034L0022

Evaporator pressure regulator, KVP 15

Product name: Evaporator pressure regulator, Type: KVP 15, Inlet size [mm]: 16.00, Inlet connection type: FLARE, Outlet size [mm]: 16.00, Outlet connection type: FLARE

PRODUCT DETAILS

Gross weight	0.47 kg
Net weight	0.42 kg
EAN	5702428411875
Approval	C UL US LISTED EAC LLC CDC TYSK
Approval file name	REFRIGERANT VALVE 53R0
Cv value [gal/min]	2.9 gal/min
Equipment	Schrader valve access port
Factory setting [bar]	2 bar
Factory setting [psig]	29 psig
Flow direction indicator	Engraved 1-way arrow
Further information	Max. extern.bellow press.26bar
Inlet connection type	FLARE
Inlet size [in]	5/8 IN
Inlet size [mm]	16 mm
Kv value [m³/h]	2.5 m^3/h
Kv value note	AT MAX P-BAND
Max. test pressure [bar]	19.8 bar
Max. test pressure [psig]	286 psig
Max. Working Pressure [bar]	18 bar
Max. Working Pressure [psig]	260 psig
Medium temperature range [°C] [Max]	130 °C
Medium temperature range [°C] [Min]	-45 °C
Medium temperature range [°F] [Max]	266 °F
Medium temperature range [°F] [Min]	-49 °F
Outlet connection type	FLARE
Outlet size [in]	5/8 IN
Outlet size [mm]	16 mm
P band max. [bar]	1.7 bar
P band max. [psi]	24.6 psi
Packing format	Multi pack
Product accessories	No
Product family name	KVP
Product group	Press. and temp. regul. valves

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

Product name	Evaporator pressure regulator
Quantity per packing format	12 pc
Rated capacity R134a [kW]	2.8 kW
Rated capacity R134a [TR]	0.9 tons
Rated capacity R22 [kW]	4 kW
Rated capacity R22 [TR]	1.3 tons
Rated capacity R404A/R507 [kW]	3.6 kW
Rated capacity R404A/R507 [TR]	1.2 tons
Rated capacity R407C [kW]	3.7 kW
Rated capacity R407C [TR]	1.2 tons
Refrigerant oil compatibility	Oilfree applications R1234ze(E) R513A
Refrigerants	R134a R22 R404A R407A R407C R407F R422B R422D R448A R449A R450A R452A R507A R513A R1234ze R407H R449B R454C R455A R515B R516A R1234yf R454A
Regulation range [bar] [Max]	5.5 bar
Regulation range [bar] [Min]	0 bar
Regulation range [psig] Pe [Max]	80 psig
Regulation range [psig] Pe [Min]	0 psig
Serviceable	KV valves spare parts
Type	KVP 15

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.