034L0042

Crankcase pressure regulator, KVL 15

Product name: Crankcase pressure regulator, Type: KVL 15, Inlet size [mm]: 16.00, Inlet connection type: FLARE, Outlet size [mm]: 16.00, Outlet connection type: FLARE

PRODUCT DETAILS

Gross weight	0.47 kg
Net weight	0.4 kg
EAN	5702428411776
Approval	C UL US LISTED EAC LLC CDC TYSK RoHS RoHS China
Approval file name	REFRIGERANT VALVE 53R0
Cv value [gal/min]	3.7 gal/min
Equipment	
Factory setting [bar]	2 bar
Factory setting [psig]	29 psig
Flow direction indicator	Engraved 1-way arrow
Further information	Max. extern.bellow press.26bar
Identical product	034L1242
Inlet connection type	FLARE
Inlet size [in]	5/8 IN
Inlet size [mm]	16 mm
Kv value [m^3/h]	3.2 m^3/h
Lubricants compatibility	Oilfree applications
Max. test pressure [bar]	19.8 bar
Max. test pressure [psig]	286 psig
Max. Working Pressure [bar]	18 bar
Max. Working Pressure [psig]	260 psig
Medium temperature range [°C] [Max]	130 °C
Medium temperature range [°C] [Min]	-60 °C
Medium temperature range [°F] [Max]	266 °F
Medium temperature range [°F] [Min]	-76 °F
Oil free refrigerants	R1234ze(E);R513A
Outlet connection type	FLARE
Outlet size [in]	5/8 IN
Outlet size [mm]	16 mm
P band max. [bar]	2 bar
P band max. [psi]	29 psi

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

Packing format	Multi pack
Product accessories	No
Product family name	KVL
Product group	Press. and temp. regul. valves
Product name	Crankcase pressure regulator
Quantity per packing format	12 pc
Rated capacity R134a [kW]	5.3 kW
Rated capacity R134a [TR]	0.8 tons
Rated capacity R22 [kW]	7.1 kW
Rated capacity R22 [TR]	1.2 tons
Rated capacity R404A/R507 [kW]	6.3 kW
Rated capacity R404A/R507 [TR]	1 tons
Rated capacity R407C [kW]	6.5 kW
Rated capacity R407C [TR]	1.1 tons
Refrigerant oil compatibility	Oilfree applications R1234ze(E) R513A
Refrigerants	R134a R22 R404A R407A R407C R407F R422B R422D R448A R449A R450A R452A R507A R513A R1234ze R407H R449B R454C R455A R515B R516A R1234yf R454A
Regulation range [bar] [Max]	6 bar
Regulation range [bar] [Min]	0.2 bar
Regulation range [psig] Pe [Max]	87 psig
Regulation range [psig] Pe [Min]	3 psig
Serviceable	KV valves spare parts
Type	KVL 15

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.