Dual Pistons Refrigerant Recovery Machine

Product Description

The MRM75 is an efficient, and reliable refrigerant recovery machine with a compact, sturdy casing. Dual pistons provides an ideal solution for making refrigerant recovery fast and efficient.

Different from most brands of refrigerant recovery machines, it adopts overhead pressure gauge and operating key design. In addition, there has a service port at the back of the machine, so it will be very convenient to replace the piston ring and air valve core. Bringing a more user-friendly user experience.

At the same time, this recovery machine can cover A2L grade refrigerants and backward compatible with these older refrigerants (such as R12, R22, and R410A).

MRM75 Refrigerant Recovery Machine

A2L Class R32 compatible

Fast Recovery, Efficient & Reliable

Built-in oil separator (MRM75OS)

Oil-free compressor with high efficient

Overhead digital display for easy reading the exact data

A easy access port at the back of machine for fast maintenance

Model	MRM75 / MRM75OS					
Refrigerant	III: R12, R134A, R401C, R406A, R500, R1234yf IV:R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509 V: R402A, R404A, R407A, R407B, R410A, R507, R32			Automatic Safety Shut-off	38.5bar/3850kpa(558psi)	
Voltage	100-120V~/50-60Hz	230V~/50-60Hz		Recovery Rate	III	IV	V
Motor Power	1.3HP				Vapor 0.5 kg/min	0.7 kg/min	0.7 kg/min
Motor Speed	3000RPM				Liquid 2.6 kg/min	3 kg/min	3.9 kg/min
Current(Max.)	13A	6.5A			Push/Pull 8.2 kg/min	9.3 kg/min	10.5 kg/min
Compressor	Oil-less, Air-cooled, Piston-style			Operating Temperature	0°C-40°C		
				Dimensions	386mm(L)*255mm(W)*276mm(H)		
				Weight	11.6 kg		
				Packing	Carton:1pc		

Accessories

1.8m power cord

Filter

Shoulder Strap

Hose